



**MULTI-PURPOSE LUBRICANT**

**DESCRIPTION AND USES**

Rust-Oleum® Multi-Purpose Lubricant lubricates and protect vital metal components. This lubricant frees rusted and corroded parts and leaves behind a protective lubricating, anti-rust film that resists water wash-off for lasting protection.

**For Professional Use Only.**

**FEATURES**

- Convenient and versatile general purpose lubricant
- Lubricates and drives out moisture
- Large 16 oz. aerosol with 360° spray tip
- Leaves behind a protective film that resists moisture

**PRODUCTS**

SKU	Description
273759	16 oz. fill weight aerosol
274825	16 oz. fill weight aerosol (Canada Only)

**PRODUCT APPLICATION**

**APPLICATION**

Use in a well ventilated area when temperatures are between 50-90°F (10-32°C). Avoid spraying in very windy and dusty conditions.

Shake well before and during use. Hold can 10-16" from the surface and spray in a steady back-and-forth motion and allow a few minutes for penetration before attempting to loosen parts. Repeat as necessary for areas with heavy deposits. Do not apply to painted surfaces, plastic, or parts made of rubber.

**PRECAUTION**

Vapors may ignite explosively. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. Avoid contact with eyes and skin.

**CLEAN UP**

Properly dispose of container and unused contents in accordance with local, state and federal regulations.

**STORAGE**

Store in cool dry areas and protect from excessive heat.

**PHYSICAL PROPERTIES**

Physical Properties	MULTI-PURPOSE LUBRICANT
Composition	Kerosene, Naphthenic Oil, Stoddard Solvents
Fill Weight	16 ounces
Shelf Life	5 years
Flash Point	-141°F (-96°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.