



DRY PTFE LUBRICANT

DESCRIPTION AND USES

Rust-Oleum® Dry PTFE Lubricant is a dry, non-oily lubricant that will not pick up dirt or dust. This PTFE formula provides excellent lubrication that will not become gummy or melt below 500°F. This product is non-staining and contains no silicone and will not interfere with paint adhesion.

For Professional Use Only.

FEATURES

- Not staining
- Does not attract dirt or dust
- Convenient aerosol with 360° spray tip
- Odorless
- Can be used on metal, wood, vinyl or rubber

PRODUCTS

SKU	Description
273925	11 oz. fill weight aerosol
274833	11 oz. fill weight aerosol (Canada only)

SURFACE PREPARATION

Surfaces must be dry and free of grease, oil, dirt, rust, wax or other forms of surface contamination.

PRODUCT APPLICATION

APPLICATION

Use in a well ventilated area when temperatures are between 50-90°F (10-32°C). Avoid spraying in very windy and dusty conditions.

Shake well before and during use. Hold can 10-16" from the surface and spray in a steady back-and-forth motion and apply an even, uniform film on all metal surfaces requiring lubrication. Repeat as necessary.

PRECAUTION

Vapors may ignite explosively. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. Avoid contact with eyes and skin.

CLEAN UP

Properly dispose of container and unused contents in accordance with local, state and federal regulations.

STORAGE

Store in cool dry areas and protect from excessive heat.

PHYSICAL PROPERTIES

Physical Properties	DRY PTFE LUBRICANT
Composition	Polytetrafluoroethylene
Solvent	Acetone, Ethylbenzene, Naphtha, Xylene
Fill Weight	11 ounces
Shelf Life	5 years
Flash Point	-141°F (-96°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.